



Safety Data Sheet

1 Identification of the Substance/Preparation and Company

PRODUCT NAME: LATEX SEAMING ADHESIVE
PRODUCT CODE: STK 800

Reviewed on 23.03.2010

Interfloor Ltd.
Broadway,
Haslingden,
Rossendale,
Lancashire
BB4 4LS

Tel: 01706 213131
Fax: 01706 214737

www.stikatak.co.uk
www.interfloor.com

2 HAZARDS IDENTIFICATION

Low hazard expected under normal conditions of use

3 COMPOSITION / INFORMATION ON INGREDIENTS

Modified water based dispersion of Natural Rubber Latex and other additives. No known hazards.

4 FIRST- AID MEASURES

CONTACT WITH SKIN

- After contact with skin, wash immediately with plenty of soap and water. Remove any contaminated clothing. May cause skin irritation
- Do not use solvents to clean skin
- Seek medical attention if irritation persists

CONTACT WITH EYES

- In case of contact with eyes, rinse immediately with plenty of water for about 15 minutes with eyelids held open. Seek medical advice.

INGESTION

- Immediately rise mouth thoroughly and drink plenty of water. Seek medical attention.
- Do not induce vomiting due to the risk of aspiration into the lungs

INHALATION

- Keep patient calm and remove to fresh air. Seek medical attention if required
-

5 FIRE-FIGHTING MEASURES

Aqueous dispersions will not burn. Dried films are combustible. Water, foam, carbon dioxide or dry powder extinguishers are all suitable. Do not inhale the fumes of burning product

6 ACCIDENTAL RELEASE MEASURES

- Prevent entry into sewers or waterways.
 - Residues and spillages should be soaked up with an inert absorbent material such as sand and disposed of appropriately
 - Small spillages may be washed away with water. Waste water must be disposed of correctly
 - Wear protective clothing
-

7 HANDLING AND STORAGE

Handling

- The usual precautions for handling chemicals should be observed
- Avoid contact with skin and eyes

Storage

- Keep container tightly closed and dry
- Store above 5°C
- Do not store above 30°C

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

- Wear suitable protective clothing, including eye/face protection and gloves (plastic or rubber are recommended)
- No exposure limits have been set for this product

9 PHYSICAL PROPERTIES

- Off white liquid miscible with water
- Non combustible
- Boiling point 100°C
- Freezing point 0°C
- pH 8-9
- Specific gravity 1.0
- Viscosity 4 000 cps @ 20-22°C

10 STABILITY AND REACTIVITY

- Stable
- Miscible with water
- No hazardous reactions known if used for it's intended purpose
- Sensitive to freezing conditions

11 TOXICOLOGICAL INFORMATION

Long term experience of handling of this type of product under industrial conditions indicates the absence of any chronic or acute effects

12 ECOLOGICAL INFORMATION

The material should not be passed into rivers or watercourses without pre-treatment. It is not readily biodegradable.

13 DISPOSABLE CONSIDERATIONS

Disposal should be in accordance with local, state or national legislation

14 TRANSPORT REGULATIONS

The material is not classified as dangerous goods

15 REGULATORY INFORMATION

- EEC Hazard Classification- None
- Handle in accordance with good industrial hygiene and safety practice

16 OTHER INFORMATION

For intended use and applications see The Technical Data Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations

· **Department issuing data specification sheet:** Quality Control

· **Contact:**

Scott Yarrow
Tel 0208 839 4405
Fax 0208 842 1387
e-mail: scottarrow@stikatak.co.uk